

24 STF6A SPECIFICATION SHEET

CASE

Style: RSC

Spec number: 49644

Size: 420 × 240 × 440mm

Minimum order quantity: 260

Pallet quantity: 65

The case holds a 4GV UN certification – see table for maximum packaging weights.

	4G pack packing group max weights			4GV pack max weight
	I (X)	II (Y)	III (Z)	
STF6A	N/A	N/A	N/A	12kg

INNER PLASTIC LINER

Liner spec number: 798126

Gusseted 2.5 litre liner

Size: 790 (length) × 457 (width) × 685 (open width) mm

Thickness: 75 micron.

NOTE

The plastic liner is only required for the 4GV version of this pack.

When ordering the 2.5 litre liner quote the size and thickness.

<p><small>U.S. PATENT PENDING FULL INSTRUCTIONS FOR THE USE OF THIS PACK ARE GIVEN ON WWW.DSS.COM/STF6A/CASE-UP PLEASE TO FOLLOW THE INSTRUCTIONS AND RESERVE THE PACK INFORMATION AREA DO NOT REUSE PACKS IN THE FIELD OR CONTACT WITH THE END USER/REMARKS OF THE U.S. COMMERCE DEPARTMENT OF COMMERCE UNDER THE REGULATORY REGULATIONS THE U.S. IS APPROVED FOR THE PURPOSES OF EXPORTS OF GOODS AS SHOWN ON THE CASE FOR RETAIL PURCHASE ONLY LABELLING OF THE PACK IS TO BE IN ACCORDANCE WITH THE RELEVANT INSTRUCTIONS. THE U.S. MARK IS NOT TO BE REUSED.</small></p>		<p>THIS SIDE UP</p>					
<p>DSSmith Tri-Wall HIGH PERFORMANCE PACKAGING</p> <p>Safe Pak</p>		<p>UN 4GV/X12/S/09/GB/1607</p> <p>Safe Pak</p>					
<p><small>4G Packing group max weights</small></p> <table border="1"> <thead> <tr> <th>Packing group</th> <th>Max weight</th> </tr> </thead> <tbody> <tr> <td>STF6A</td> <td>N/A</td> </tr> </tbody> </table>	Packing group	Max weight	STF6A	N/A			
Packing group	Max weight						
STF6A	N/A						