

28 STF8A SPECIFICATION SHEET

CASE

Style: RSC

Layer pad × 2 in 510 CA
(only required for 4GV version of pack)

Spec number: 49646

Size: 600 × 600 × 440mm

Minimum order quantity: 260

Pallet quantity: 65

The case holds a 4GV UN certification –
see table for maximum packaging weights.

	4G pack packing group max weights			4GV pack max weight
	I (X)	II (Y)	III (Z)	
STF8A	N/A	N/A	N/A	45kg

INNER PLASTIC LINER

Liner spec number: 798124

Gusseted 10 litre liner

Size: 1390 (length) × 770 (width) × 1300 (open width) mm

Thickness: 125 micron.

NOTE

The plastic liner is only required for the 4GV version of this pack.
When ordering the 10 litre liner quote the size and thickness.

<p><small>D.S. SMITH TRI-WALL ALL INFORMATION FOR THE USE OF THIS PAGE ARE GIVEN ON WEB SITE OR BY TELEPHONE 01223 312121</small></p> <p><small>PLEASE FOLLOW THE INSTRUCTIONS HERE. INSTRUCTIONS WILL BE GIVEN TO YOU BY THE CUSTOMER SERVICE TEAM.</small></p> <p><small>IF YOU ARE USING THIS PACK TO TRANSPORT A LIQUID OR SOLID IN A LIQUID OR SOLID STATE, PLEASE FOLLOW THE RELEVANT REGULATIONS AND INSTRUCTIONS FOR THE TRANSPORT OF DANGEROUS GOODS AND THE RELEVANT REGULATIONS.</small></p> <p><small>THIS PACK IS NOT TO BE USED FOR THE TRANSPORT OF A LIQUID OR SOLID IN A LIQUID OR SOLID STATE. PLEASE FOLLOW THE RELEVANT REGULATIONS AND INSTRUCTIONS FOR THE TRANSPORT OF DANGEROUS GOODS AND THE RELEVANT REGULATIONS.</small></p> <p><small>LABELLING OF THE PACK IS TO BE IN ACCORDANCE WITH THE RELEVANT REGULATIONS. THE UN MARK IS NOT TO BE OBLITERATED.</small></p>		<p>THIS SIDE UP</p>											
<p>DSSmith Tri-Wall HIGH PERFORMANCE PACKAGING</p> <p>Safe Pak</p>	<p>STF8/A</p>	<p>4GV/X45/S/09/GB/1386</p> <p>Safe Pak</p>	<p>STF8/A</p>										
<table border="1"> <thead> <tr> <th>4G Packing group max weights</th> <th>4GV pack max weight</th> </tr> </thead> <tbody> <tr> <td>Class I (X)</td> <td>45kg</td> </tr> <tr> <td>Class II (Y)</td> <td></td> </tr> <tr> <td>Class III (Z)</td> <td></td> </tr> <tr> <td>STF8A</td> <td>N/A</td> </tr> </tbody> </table>	4G Packing group max weights	4GV pack max weight	Class I (X)	45kg	Class II (Y)		Class III (Z)		STF8A	N/A			
4G Packing group max weights	4GV pack max weight												
Class I (X)	45kg												
Class II (Y)													
Class III (Z)													
STF8A	N/A												